

Thunderbird configuration

Table of Contents

- [Introduction](#)
- [Config Editor](#)
- [Default web browser](#)
- [Gmail client](#)
- [IMAP settings](#)
 - [Show Only Subscribed Folders](#)
 - [Subscribing](#)

Introduction

TBC

Config Editor

The Config Editor is accessed via PreferencesPreferencesAdvancedGeneralConfig Editor.

Default web browser

Thunderbird defaults to using the desktop's default web browser. To override this setting, use the config editor (below) to ensure network.protocol-handler.app.http and https exist with the path to the desired browser program. For example, for firefox (⚠️ this did not work on Ubuntu 12.04 Precise):

```
network.protocol-handler.app.http, string, /usr/bin/firefox
```

```
network.protocol-handler.app.https, string, /usr/bin/firefox
```

Gmail client

There's a Mozilla KB page on configuring Thunderbird as a Gmail client, listed in the Reference section below.

IMAP settings

Server Settings -> Advanced -> Show Only Subscribed Folders

In Config Editor (above):

- **mail.imap.auto_unsubscribe_from_noselect_folders** Default and desired value: true
- **mail.server.default.check_all_folders_for_new** Default false. Setting it true avoids the user having to wait for mails to be downloaded on opening folders other than the Inbox – but it may degrade overall performance, especially when Thunderbird is started. When the IMAP server is local it should be OK. In case of several IMAP servers, the setting can be made for specific servers using **mail.server.server<n>.check_all_folders_for_new**

Show Only Subscribed Folders

Account SettingsServer SettingsAdvancedShow Only Subscribed Folders

Subscribing

Depending on the setting of "Show Only Subscribed Folders", folders on the server that Thunderbird is not subscribed to are invisible or shown greyed out.

To subscribe to folders, right click any folder and choose Subscribe. Expand the list until the folders you want to subscribe are visible, toggle (✓) the checkbox and click Subscribe.